


SOFFITTO / CEILING


BEAM MASTER Ø25







Alluminio
Fascio di luce orientabile
Driver: escluso

Aluminum
 Light beam: adjustable
 Driver: excluded

**Corpo (ghiera esclusa) / Body (ring excluded)**

	M 2700°K	W 3000°K	N 4000°K
4310			
Potenza/ Power	1x 4W	1x 4W	1x 4W
Lumen	1x 380 lm	1x 410 lm	1x 410 lm
CRI	>90	>90	>90
Alimentazione/ Supply	24Vdc	24Vdc	24Vdc




Articolo Item	Temperatura Temperature	°Ottica °Optic	Finitura Finish
4310	M	16	-BO 
	W		-NO 
	N		-BV 
			-OR 
			-RR 
			-TI 

Ghiera / Ring

Filtro anti-abbagliamento incluso
 Antiglare filter included



Articolo Item	Finitura Finish
410	-BO 
	-BV 
	-NO 
	-OR 
	-RR 
	-TI 

Alimentatori 24Vdc in tensione in remoto / Remote constant voltage drivers 24Vdc

Articolo Item	Potenza Power	Dimensioni Dimensions	N° art. alimentabili N° of items powerable
1A0150	30W	160x58x18	1-4
1A0151	50W	160x58x18	1-6
1A0152	75W	160x58x18	1-9
1A0145	100W	190x52x37	1-12
1A0153	150W	240x60x49	1-18

Centraline dimmerabili in remoto / Remote dimmable controllers

Articolo Item	Potenza Power	Dimensioni Dimensions
1A0837	120W MAX	132x22x19
1A0838	240W MAX	156x47x26
1A0172	240W MAX	57x43x19