

OUTDOOR

TERRA / FLOOR

MAXI DOT SPOT




- alluminio, vetro

- aluminum, glass



117	M 2700K	W 3000K	N 4000K
Potenza/ Power	1x9.4W	1x9.4W	1x9.4W
Nominal lumen	1x1090lm	1x1137lm	1x1175lm
CRI	>90	>90	>90
Alimentazione/ Supply	24Vdc	24Vdc	24Vdc




Articolo Item	Temperatura Temperature	°Ottica °Optic	Finitura Finish
117	M	00	-AA
	W	12	-BA
	N	35	-NA
		55	



Versione RGBW / RGBW version

117	RGBW RGB + 3000K
Potenza/ Power	1x7.9W
Nominal lumen	1x446lm
CRI	90
Alimentazione/ Supply	700mA



Articolo Item	Temperatura Temperature	°Ottica °Optic	Finitura Finish
117	RGBW	26	-AA
		36	-BA
		60	-NA


Accessori / Accessories

Picchetto
Peg


Articolo
Item
PC



Ghiera e visiera anti-abbagliamento
Ring and antiglare visor

512**-NA**

Cinghia di fissaggio
Fixing belt

515

Controller per versione RGBW / Controller for RGBW version

Controller 4 canali - CC
4-channels controller - CC

Articolo
Item
1A0521/01

Potenza Power	IP IP	Dimensioni Dimensions	Dimmerazione Dimming
17W	IP20	90x71x58	PUSH

Controller 4 canali - CC
4-channels controller - CC

1A0521/03

17W	IP20	90x71x58	DALI
-----	------	----------	------

Controller 4 canali - CC
4-channels controller - CC

1A0521/04

17W	IP20	90x71x58	DMX
-----	------	----------	-----

Driver 24Vdc in tensione in remoto / Remote constant voltage drivers 24Vdc

Articolo Item	art. alimentabili items powerable	Potenza Power	IP IP	Dimensioni Dimensions	Dimmerazione Dimming
1A0143	1	14W	IP67	85x39x19	ON-OFF
1A0148	1-2	30W	IP67	131x42x34	ON-OFF
1A0149	1-6	75W	IP67	155x50x32	ON-OFF
1A2386	1-8	120W	IP67	191x63x37,5	DALI
1A2387	1-10	200W	IP67	195x68x39,5	DALI PUSH