

OUTDOOR

TERRA / FLOOR

MINI DOT SPOT




- alluminio, vetro

- aluminum, glass



137	M 2700K	W 3000K	N 4000K
Potenza/ Power	1x5.8W	1x5.8W	1x5.8W
Nominal lumen	1x515lm	1x555lm	1x555lm
CRI	>90	>90	>90
Alimentazione/ Supply	24Vdc	24Vdc	24Vdc



Articolo Item	Temperatura Temperature	°Ottica °Optic	Finitura Finish
137	M	00	-AA
	W	15	-BA
	N	36	-NA


Accessori / Accessories

Articolo Item
PC

Picchetto
PegGhiera e visiera anti-abbagliamento
Ring and antiglare visor


511

-NA



Cinghia di fissaggio
Fixing belt

515



Driver 24Vdc in tensione in remoto / Remote constant voltage drivers 24Vdc

Articolo Item	art. alimentabili items powerable	Potenza Power	IP	Dimensioni Dimensions	Dimmerazione Dimming
1A0143	1	14W	IP67	85x39x19	ON-OFF
1A0148	1-2	30W	IP67	131x42x34	ON-OFF
1A0149	1-6	75W	IP67	155x50x32	ON-OFF
1A2386	1-10	120W	IP67	191x63x37,5	DALI
1A2387	1-16	200W	IP67	195x68x39,5	DALI PUSH