

Paralume in metacrilato curvato stampato spessore 8 mm. Profilati e dettagli in metallo ottonato satinato con vernice opaca. Lampada con fonte luminosa a led 2700K.

Applique 80.

Striscia LED 2700K – 20 W/MT. Alimentatore 110/240 V – 24V. 1920 lumen.

Applique 150.

Striscia LED 2700K – 20 W/MT. Alimentatore 110/240 V – 24V. 3600 lumen.

Sospensione a "U" 150.

Strip led inferiore 2700K – 14W/MT. Alimentatore 110/240V – 24V. 2250 lumen.

Strip led superiore che eccita metacrilato 2700K – 20W/MT. Alimentatore 110/240V – 24V. 3600 lumen.

Possibile dimmerazione previa richiesta all'ufficio tecnico e conseguente preventivo.

8 mm thick lampshade in printed curved methacrylate. Profiles and details in satin brass-coated metal with matte varnish. Lamp with 2700K led light source.

Wall lamp 80.

2700K LED strip – 20W/MT. 110/240V – 24V power supply. 1920 lumens.

Wall lamp 150.

2700K LED strip – 20W/MT. 110/240V – 24V power supply. 3600 lumens.

"U" hanging lamp 150.


2700K lower led-strip – 14W/MT. 110/240V – 24V power supply. 2250 lumens.

2700K upper led-strip that energizes methacrylate – 20W/MT. 110/240V – 24V power supply. 3600 lumens.

Dimming is possible subject to request to the technical department and consequent quotation.


14 x 12 h80

Applique. Wall lamp.



26 x 20 h150

Applique. Wall lamp.



150 x 33 h36

Sospensione. Hanging lamp.

