



Wrap P

design Balutto Associati, 2016

Wrap chair with four legs base in white or graphite lacquered steel. Shell upholstered in leather, ecoleather, fabric or custom's fabric.



Finishing and Materials

Structure



White Steel



Grafite Steel

Coating



Inca Ecoleather
17 colors



Magic Ecoleather
17 colors



Vintage Ecoleather
4 colors



Fiore Leather
15 colors



Vintage Leather
4 colors



Pix Fabric
13 colors



Mirage Fabric
16 colors



Natural Wool Fabric
15 colors



Long Life Fabric
13 colors



Bubble fabric
14 colors



Hot Fabric
13 colors

Dimensions



Dimension	cm	inch
A	80	31.5

Dimension	cm	inch
B	60	23.6
C	55	21.7
D	46	18.1

Volumetric Details

Weight 18
Volume 0.48 mc
Package 1

Gallery



Downloads

3D Wrap P (zip) - http://www.midj.com/images/uploads/resources/WRAP_P.zip

Materials Certifications

Inca Ecoleather	Martindale: 50.000 cycles Composition: 6% Cotton, 6% Polyester, 88% PVC Shrinking about: 1% Fire retardant fabric: Classe 1IM, BS 5852 Part. 1, IMO RES. A.652(16)
Magic Ecoleather	Martindale: 150.000 cycles Composition: 31% Cotton, 48% Polyurethane, 21% Polyester Shrinking about: 1% Fire retardant ecoleather: Classe 1IM, BS 5852 Part. 1, Cigaret Test, Match Test
Vintage Ecoleather	Ecoleather phtalatic free - R.E.A.C.H. 1907/2006/EU Breathable ecoleather Composition: 90% PVC, 7% Polyurethane, 3% Cotton Shrinking about 1%
Fiore Leather	BS 5852 parte 1; ISO 5402>50000 cicli; ISO 105B02 ? 5; ISO 3377-1 ?20 N; ISO 11644 ? 2.5 N/Cm; EN 1021/1-2; EN ISO 17233 -20°; IMO RES A 6528(16)

Vintage Leather	UNI EN ISO 105 B02 ?3; ISO 5402>50000 cicli; ISO 3377-1?20; UNI EN ISO 11640 Secco - Dry 50 c ?4 Umido - Wet 20 c ? 3; Sudore - Sweat 20 c ? 3
Mirage Fabric	Martindale: 100.000 cycles Composition: 100% Polyester Shrinking about 1% Fire retardant fabric: classe 1IM, B1 DIN 4102, M1, B1 OENORM Part.1, BS 5852 Crib 5, EN 1021, USA Calif. Bull 117, IMO 688 (17) - IMO 563 (14) - IMO 653 (16)
Natural Wool Fabric	Martindale: 100.000 cycles Composition: 70% Wool, 25% Polyamid, 5% Fibers Shrinking about: 1% Fire retardant fabric: BS 5852 part. 1, Cigaret test, Match test
Long Life Fabric	Martindale 40.000 cycles Composition: 74% Polyester, 18% Cotton, 8% Acrylic Shrinking about 1%
Bubble fabric	Martindale: 35.000 cycles Composition: 100% Pes Fire retardant fabric: BS5852:2006 (p. 11 CRIB 5), EN1021-1, EN1021-2, UNI 9175:2010 - classe 1 im
Hot Fabric	Martindale: 45.000 cycles Composition: 100% Pes Fire retardant fabric: BS5852:2006 (p. 11 CRIB 5), EN1021-1, EN1021-2, UNI 9175:2010 - classe 1 im