



DESCRIPTION Beak Ceiling Point emits a focused, defined beam of direct light from a static cylindrical body in burnished brass. Its compact geometry is distinguished by a fully knurled surface that introduces visual rhythm. Also available in a Flat version with a reduced thickness canopy, it ensures discreet ceiling integration, making it suitable even for contract settings. Beak is also available in floor, table, suspension, wall versions and another ceiling model.

PRODUCTS DETAILS	FUNCTION	CEILING
	LOCATION	INTERIOR
	LIGHT EMISSION	DIRECTIONAL LIGHT
	LIGHT SOURCE	COB LED CLU703 6W 724lm 700mA 9V CRI90 2700°K
	ENERGY EFFICIENCY	F
	RATED VOLTAGE	110 - 120 V / 220 - 240 V
	FREQUENCY	50 - 60Hz
	SUPPLY	BEAK CEILING POINT TERMINAL BLOCK BEAK CEILING POINT FLAT REMOTE TERMINAL BLOCK
	LENS SPOT BEAM	18° - 36° - 60°
		BEAK CEILING POINT: DALI or TRIAC dimming kit available upon request BEAK CEILING POINT FLAT: DALI or TRIAC remote dimming kit available upon request

CERTIFICATION



MATERIALS

STRUCTURE	
M11	LIGHT BURNISHED BRASS
M12	DARK BURNISHED BRASS


PACKAGE	QTY	DIMENSIONS	NET WEIGHT	GROSS WEIGHT	TOTAL VOL.
-	-	-	-	-	-

DIMENSIONS

BEAK CEILING POINT



STANDARD

Ø 9 cm (3"5)



J-BOX KIT


Ø 14 cm (5"5)



BEAK CEILING POINT FLAT

STANDARD

Ø 8 cm (3"1)



J-BOX KIT

Ø 11 cm (4"3)

